AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application.

LISTING OF CLAIMS:

Claims 1, 2, 3, 4, 5, 6:	Canceled
Claim 7.	Canceled

Claim 8. (previously presented)

Sprinkler apparatus comprising:

a base adapted for attachment to a sprinkler assembly,

a nozzle mounted on said base,

said nozzle having a passage adapted to provide a liquid jet of a generally rectilinear cross-sectional configuration,

means to supply liquid under pressure to the nozzle,

a reflector surface disposed to be impacted by said liquid output jet from the nozzle,

said nozzle and reflector surface being defined on a unitary nozzle device which is force-fitted into the base,

said reflector surface being adapted and contoured to reflect said liquid jet in a spray to an area to be sprayed, said spray being of cross-sectional configuration generally similar to the rectilinear cross-sectional configuration of said liquid jet,

(continued)

Claim 8. (previously presented - continued)

the reflector surface having variations in the surface to reflect respective portions of spray at respective inclinations from the reflector to define respective portions of a predetermined spray pattern to respective portions of an area to be sprayed,

whereby a spray pattern of a predetermined rectilinear cross-sectional configuration from the reflector surface is applied to the area to be sprayed.

Claim 9. (original)

Apparatus according to Claim 8, wherein the surface configuration of the reflector is generally convex in two directions substantially at right angles to each other.

Claim 10. (original)

Apparatus according to Claim 9, wherein variations in the general convex contour of the reflector surface to effect respective inclinations of spray portions, may be determined (a) emperically, (b) preferably by utilization of computer equipment and insertion thereinto of data including geometric relations of parts, angles, and dimensions.

Claim 11. (original)

Apparatus according to Claim 8, wherein the reflector surface is defined on a flexible member on the apparatus, and further including:

a threaded member in an opening in the apparatus for adjustment of the configuration of the reflector.

Claim 12. (previously presented)

Apparatus according to Claim 8, wherein a step shoulder is defined in a wall portion of the nozzle apparatus adjacent an outlet end of the nozzle passage to deflect the liquid jet from an innermost portion of the reflector surface to prevent interference by inaccurate spray from the innermost reflector surface portion.

Claim 13. (previously presented)

Apparatus according to Claim 8, wherein the nozzle and reflector surface are defined on the unitary nozzle device having portions thereof adapted to be snapped into an upper portion of the base to mount the nozzle device on the base.

Claim 14. Canceled

Claim 15. Canceled.

Claim 16. (previously presented)

Sprinkler apparatus comprising:

a base adapted for attachment to a sprinkler and for liquid passage therethrough,

a unitary nozzle device mounted on said base,

said unitary nozzle device comprising an integrally formed nozzle passage and an integral reflector surface disposed in spaced-apart confronting relation, said reflector surface being disposed to be impacted by a liquid jet from the nozzle passage,

said unitary nozzle device providing dimensional accuracy as between the nozzle and the reflector surface to enable accurate performance of the nozzle device and accurate repeatability in manufacture of the device,

said nozzle passage being adapted to provide the liquid jet in a generally predetermined cross-sectional configuration,

(continued)

Claim 16. (previously presented - continued)

said reflector surface being contoured and adapted to reflect said liquid jet in a spray to an area having a cross-sectional configuration to be sprayed which is generally similar in cross-sectional configuration to that of said liquid jet, and

a step shoulder defined in a wall portion of the nozzle device adjacent an outlet end of the nozzle passage to deflect the liquid jet from an innermost portion of the reflector surface to prevent interference by inaccurate spray from the innermost reflector surface portion,

whereby a spray pattern of a substantially predetermined cross-sectional configuration is applied to an area to be sprayed.

Claim 17. Canceled

Claim 18. Canceled

Claim 19. Canceled

Claim 20. (previously presented)

Sprinkler apparatus comprising:

a base adapted for attachment to a sprinkler and for liquid passage therethrough,

a unitary nozzle device mounted on said base,

said unitary nozzle device comprising an integrally formed nozzle passage and an integral reflector surface disposed in spaced-apart confronting relation, said reflector surface being disposed to be impacted by a liquid jet from the nozzle passage,

said unitary nozzle device providing dimensional accuracy as between the nozzle and the reflector surface to enable accurate performance of the nozzle device and accurate repeatability in manufacture of the device,

a generally circular lower portion of the nozzle device being force-fitted into a circular opening in the base, and wherein an interior wall of the base provides a wall of the nozzle passage,

(continued)

Claim 20. (previously presented - continued)

said nozzle passage being adapted to provide the liquid jet in a generally predetermined cross-sectional configuration, and

said reflector surface being contoured and adapted to reflect said liquid jet in a spray to an area having a cross-sectional configuration to be sprayed which is generally similar in cross-sectional configuration to that of said liquid jet,

whereby a spray pattern of a substantially predetermined cross-sectional configuration is applied to an area to be sprayed.

Claims 21, 22, 23, 24: Canceled